

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einza Härter Lawiment, 2-K-PU Mattsiegel

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H332

Aquatic Chronic 3; H412

Resp. Sens. 1; H334

Skin Sens. 1; H317

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

Phosphoric acid, bis(2-ethylhexyl) ester, compd. with N,N-diethylethanamine (1:1), reaction products with polyethylene glycol mono-Me ether-blocked 1,6-diisocyanatohexane homopolymer and triethylamine mono-Bu phosphate (1:1)

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

tosyl isocyanate

Hazard statement(s)

- H317 May cause an allergic skin reaction.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/eye protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P405 Store locked up.
- P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

- PBT assessment
The components of this product are not considered to be a PBT.
- vPvB assessment
The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	Phosphoric acid, bis(2-ethylhexyl) ester, compd. with N,N-diethylethanamine (1:1), reaction products with polyethylene glycol mono-Me ether-blocked 1,6-diisocyanatohexane homopolymer and triethylamine mono-Bu phosphate (1:1)			
	2450971-04-5 861-035-2 - -	Skin Sens. 1; H317 Acute Tox. 4; H332 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 70.00 - < 90.00	wt%
2	(2-METHOXYMETHYLETHOXY)PROPANOL			
	34590-94-8 252-104-2 - 01-2119450011-60	-	>= 10.00 - < 25.00	wt%
3	tosyl isocyanate			
	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47	EUH014 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Irrit. 2; H315 STOT SE 3; H335	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

According to the information provided in the supply chain, the monomeric diisocyanate content is < 0.1 %.

SECTION 4: First aid measures

4.1 Description of first aid measures

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Nitrogen oxides (NO_x); Hydrogen cyanide (HCN); Monomeric isocyanates; Amines; alcohols; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant.

One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts), concentrated (d = 0,880) ammonia solution (5 parts).

A non-flammable alternative is sodium carbonate (5 parts), water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to local regulations (see section 13).

6.4 Reference to other sections

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this mixture is used. Examination of lung function should be carried out on a regular basis on persons spraying this mixture. Care should be taken when re-opening partly used containers. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO₂ will be formed which in closed containers can result in pressurisation. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. Welding, grinding and other hot work on the already-coated substrate may cause free isocyanates to be formed and released. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials as well as amines, alcohols and water.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8	252-104-2
	2000/39/EC		
	(2-Methoxymethylethoxy)-propanol		
	WEL long-term (8-hr TWA reference period)	308	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	(2-Methoxymethylethoxy) propanol		
	WEL long-term (8-hr TWA reference period)	308	mg/m ³ 50 ppm
	Comments	Sk	
2	tosyl isocyanate	4083-64-1	223-810-8
	List of approved workplace exposure limits (WELs) / EH40		
	Isocyanates, all (as -NCO) Except methyl isocyanate		
	WEL short-term (15 min reference period)	0.07	mg/m ³
	WEL long-term (8-hr TWA reference period)	0.02	mg/m ³

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

Comments	Sen
----------	-----

Other information

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application.

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Air-fed protective respiratory equipment must be worn by spray operator even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. If dry flattening is unavoidable air fed respiratory protective equipment should be used. When spraying: air fed respirator. For operations other than spraying: In well ventilated areas, air-fed respirators could be replaced by a combination of charcoal filter and particulate filter mask. Filter A2P2 (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
characteristic	
pH value	
No data available	
Boiling point / boiling range	
Value	appr. 100 °C

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

Melting point/freezing point	
No data available	

Decomposition temperature	
No data available	

Flash point	
Value	65 - 68 °C
Method	closed cup

Ignition temperature	
No data available	

Oxidising properties	
Not applicable	

Flammability	
Not applicable	

Lower explosion limit	
No data available	

Upper explosion limit	
No data available	

Vapour pressure	
Value	< 100 hPa
Reference temperature	50 °C

Relative vapour density	
No data available	

Relative density	
No data available	

Density	
Value	1.11 - 1.12 g/cm ³
Reference temperature	20 °C
Method	DIN 51757

Solubility in water	
Comments	miscible

Solubility	
No data available	

Partition coefficient n-octanol/water (log value)	
No data available	

Kinematic viscosity	
Value	50 - 60 sec
Reference temperature	20 °C
Method	DIN EN 2431 (4 mm)

Solvent separation test	
Not applicable	

Particle characteristics	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

The product reacts slowly with water resulting in evolution of carbon dioxide.

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials, amines, alcohols and water. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Uncontrolled exothermic reactions occur with amines and alcohols.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products. Amines; Alcohols; Hydrogen cyanide (HCN); Monomeric isocyanates

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity	
No data available	

Acute dermal toxicity	
No data available	

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza Härter Lawiment, 2-K-PU Mattsiegel
ATE (Mixture)	13.7500 mg/l
Route of exposure / physical form	Vapour
Method	Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.

Acute inhalational toxicity	
No data available	

Skin corrosion/irritation	
No data available	

Serious eye damage/irritation	
No data available	

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity	
No data available	

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
---	--

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information

Do not allow to enter drains or water courses.

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues in empty containers should be neutralised with decontaminant (see section 6). Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3
 The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	tosyl isocyanate	4083-64-1	223-810-8	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

Trade name: einza Härter Lawiment, 2-K-PU Mattsiegel

Product no.: 0079320

Current version : 5.0.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 22.05.2023

Region: GB

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	19.00 %
-------------	---------

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : j, type: wb = 140 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 140 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH014	Reacts violently with water.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 773832