

TECHNICAL DATA SHEET No.503

Schnellspachtel

Product code	M-DF02.
Giscode	BSW20
Type of material	ready-to-use allround - acrylic filler in tubes for repair work inside and outside.
Colour shade	white
Binder basis	acrylic latex
Pigments	Filler with a grain size up to 0,03 mm
Density	approx. 1,80
Properties (improved quality)	<ul style="list-style-type: none"> • good filling properties • optimized drying characteristics • good grindable • environment-friendly • higher volume stability • very small crack formation with higher layer thickness
Application purpose	For grinding of porous surfaces, for the preparation of varnishing works inside, on wood, plaster and concrete. Preparation of hardware with Rostprimer beforehand. For outside to renovate before coating.
Coating technique	With steel Japanese spatula. Cleaning of tools immediately after use with water.
Applied strength of coating	0 - 2 mm
Drying time	Depending on the applied strength of coating dry after approx. 30 minutes and recoatable after approx. 1 - 2 hours (at 20 °C and 65 % rel. air humidity).
Working temperature	air and object temperature not below +5 °C.
Dilution	no dilution
Storage	approx. 1 year, cool but frost-free. Close opened containers tight.
Packing size	200 ml tube 750 ml tube



P.T.O.!

Security advice and labelling

The product is subject to the Ordinance on Hazardous Substances.

All necessary advices are included in the Safety Data Sheet according to the CLP regulation (GHS) corresponding the regulation (EG) no. 1272/2008. At any time available at www.einzA.com or to be requested by sdb@einzA.com.

Labeling notes on the container labels have to be considered !

The previous information has been conscientiously compiled according to the present state of knowledge of test technology and should serve as a guideline. Due to the multitude of uses and working methods, it is non-binding, does not establish any contractual legal relationship and does not release the consumer from his own responsibility of checking our products himself. Otherwise, our conditions of delivery and payment apply. Issued **03.2021**; with this, all previous specification sheets are invalid.